

Date: 13/06/2024

TEST REPORT FIRE TEST

Baaikensstraat 11, B-9240 Zele, Tel: +32(0)52/45 85 40 Fax: +32(0)52/45 85 45

	Customer		CTF2000		
	Company	HÖPKE TEXTILES	Made by	Aylin Kiran	
	Compound	FLAMAWAY CRIB 5	Function	Lab Project Coordinator	
	Description of the assembly				
	Article indicated: AMILIO Total fabric weight: 588 g/m²				
The fabric has been water soaked in accordance with BS 5651					
	FR test method for upholstered seating				
	BS 5852 : 2006 - Crib V test				
	Type of foam used for testing : CMHR35 (*)				
		Test results		<u>ults</u>	PASS Criteria
	<u>Flaming criteria</u>				
	Unsafe escalating combustion		No		No
	Test assembly consumed Flames to extremities Flame through thickness		No		No
			No		No
			No		No
	Flame time (min)		4'35"		< 10 min
Smouldering criteria					
	Unsafe escalating combustion Test assembly consumed		No		No
			No		No
	Smoulders to extremities		No		No
	Smoulders throu	gh thickness	No		No
	Smouldering time	e (min)	Na		< 60 min
	Conclusion				
	The sample meets the requirements for BS 5852- source 5.				

(*) Type of foam used for testing: CMHR35: combustion modified high resilience foam 35kg/m³

Note:

CTF 2000 - lab is not a accredited test laboratory for fire resistant testing. The test results can be used as a guidance but not for official use. The information submitted in this report is based on our current knowledge and experience.

We don't have for all FR tests the official installation as described in the standard, but for a number of tests, we imitate the test as close as possible. This data does not imply any legally binding assurance of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed

30/10/2008, doc.nr. F8023, uitgave: 1

Pagina 1 van 1