

Company:

Höpke Möbelstoff-Handels GmbH · Simonsgasse 19 - 21 · 96489 Niederfüllbach

Flame Retardant finishing to pass B1 standard

Flammability test: DIN 4102/B1			Warp			Weft		
Edge flame exposure	BT	GT	CL	BT	GT	CL	BT	GT
ARIANE PLUS SAFE-TEX								
3 sec. flame exposure	0	0	47	0	0	32		
15 sec. flame exposure	0	0	86	0	0	73		
In the DIN 54336 the burning time is indicated after 3 sec. and 15 sec. flame exposure.								
BT= burning time (sec) GT=glowing time (sec) CL=char length (mm) Class=Classification								
DIN 4102/B1 passed								

Flammability test: DIN 4102/B1			Warp			Weft		
Edge flame exposure	BT	GT	CL	BT	GT	CL	BT	GT
VARESE PLUS SAFE-TEX								
3 sec. flame exposure	0	0	44	0	0	34		
15 sec. flame exposure	0	0	85	0	0	76		
In the DIN 54336 the burning time is indicated after 3 sec. and 15 sec. flame exposure.								
BT= burning time (sec) GT=glowing time (sec) CL=char length (mm) Class=Classification								
DIN 4102/B1 passed								